

condensation on windows?
bathroom mold growth?
noisy bath/kitchen fans?

Efficient, Quiet Exhaust Ventilation For A Healthy Home


Ultra-Aire™
QUIET-VENT



P/N 4019663

- **2-Speed Fan with Timer**
- **Extremely Quiet Operation**
- **Powerful Ventilation**

EFFECTIVE AND EFFICIENT VENTILATION

The Ultra-Aire™ Quiet-Vent™ is a central exhaust ventilation system that replaces noisy, low output and unreliable bath fans. With today's tight homes, Ultra-Aire™ Quiet-Vent™ presents one of the best ways to eliminate pollutants (i.e. normal household chemicals, outgassing from construction materials, furniture and carpeting) by exhausting them out of the home. Quiet-Vent also can reduce humidity levels that otherwise lead to mildew in closets, condensation on windows, insulation and walls which, over just a few years, can cause costly damage.

Exhaust ventilation is the most effective way to ventilate your home.* By slightly depressurizing the house, exhaust ventilation prevents moisture from penetrating and damaging the structure. Therma-Stor makes the best even better by including a programmable seven day lifestyle timer on every unit. This assures ventilation when you need it and guards against wasteful ventilation of an empty house. Ventilation rates may be adjusted to provide the correct air flow rate for a variety of home and family sizes. Quiet-Vent replaces the need for noisy bath fans when ducted with bathroom intakes and optional crank-style timers.

* Lawrence Berkley Laboratory compared the performance of exhaust ventilation with air to air heat exchangers in five different climates, and found that exhaust ventilation provides better indoor air quality.

Ultra-Aire Quiet Vent Specifications

PART NUMBER:	4019663
FAN MOTOR:	2 speed, 115 volts, 60 hertz 1.7 amps, thermally protected 95 watts/high speed; 50 watts/low speed (115 volt 10 amp circuit required)
FAN CAPACITY:	.4" W.G. high speed 295 CFM .3" W.G. low speed 165 CFM
TIMER:	7-day timer; 2 hour intervals (controls low speed)
REMOTE CONTROL CIRCUIT:	115 volt (controls high speed), Prewired relay (included).Crank timer (order separately)
INLET DUCTS:	Three 4" and one 6"
OUTLET DUCT:	Single 6"
FILTER:	Metal screen (cleanable)
SOUND LEVEL:	Less than 1 sone at exhaust grill
HANGERS:	4 vibration absorbing 1 1/2" x 11" nylon reinforced rubber.
WEIGHT:	30 lbs.
DIMENSIONS:	14 1/2" (W) X 13 1/2" (L) x 13 1/8" (H)

4 PICKUP PACKAGE AND ACCESSORIES

4023349	4 pickup package. Includes 1-each: Ultra-Aire Quiet Vent, Wall Cap, Boot, Reducer and 6" x 25' Insulated Flex Duct, plus 4-each: register heads, grilles, timers and 4" foil flex duct.
4020124	Wall Cap
4020119	Boot
4020128	6" x 25' Insulated Flex Duct
4020117	4 each – Register Heads
4020126	4 each – Grilles
4020116	4 each – Crank Timers (standard white)
4020129	4 each – 4" foil flex

